



Spraybuff

water-based shine maintainer

Spraybuff is a blend of detergents and polymers that removes black heel and scuff marks without disturbing the finish on the floor. Use of Spraybuff minimizes floor care maintenance and restores shine.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

CLEANS AND SHINES IN ONE OPERATION:

Spraybuff is formulated by using a floor finish polymer blended with a high-quality detergent for removing scuffs, black heel marks, and scratches without disturbing the finish on the floor.

MINIMIZE MAINTENANCE:

Spraybuff minimizes floor care maintenance expenditures by reducing the cost of stripping, sealing, and refinishing. Spray buffing provides important preventive maintenance when used to restore traffic lanes, to remove scratches, or to add a high gloss to an already waxed or finished floor.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before use, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

1. Dust and damp mop floor thoroughly.
2. Spray Spraybuff lightly over a 4 ft. square area in front of, or alongside, the floor machine. Too much Spraybuff will take more time than needed, so just mist the area.
3. Start buffing the Spraybuff immediately, moving the machine left to right or back and forth. When floors have been buffed dry, turn pad over and buff to a high gloss. Spraybuff may be used with floor machines of all speeds.

4. After you have finished Spraybuffing, dust mop the floor using Spartan's Dust Mop/Dust Cloth Treatment and damp mop if necessary.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Specific Gravity –0.996 @ 24°C/ 75°F

pH (Concentrate) – 10.0 – 10.5

Density –8.3 lbs./gal. @ 24°/ 75°F

Stability:

- a. Storage @ 24°/75°F – One year minimum
- b. Accelerated @ 49°/120°F – 60 days minimum
- c. Freeze/Thaw – Can withstand 3 cycles



ISSA MEMBER
The Experts
on Cleaning and Maintenance

Distributed by:

HDI

1890 Chrysler Dr.
Belvidere, IL 61008
815-547-3737
sales@2hdi.com
www.HDi3.com

PACKAGING

444065	330-gallon totes
444055	55-gallon drum
444030	30-gallon drum
444015	15-gallon drum
444005	5-gallon pail
444004	1-gallon (4 per case)
304003	1-quart (12 per case)



Label copy is provided in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product available worldwide. For institutional and industrial use only.

© SCC 5/11 L4440